



# DOSAFOS MIGNON PLUS SL


## WORKING CONDITIONS

Max working pressure \_\_\_\_\_ 8 bar (116 psi)  
Max working temperature \_\_\_\_\_ 35°C (95°F)  
Min working temperature \_\_\_\_\_ 4°C (39,2°F)  
Max total hardness \_\_\_\_\_ 50°F (500 ppm CaCO<sub>3</sub>)

**Remark** - Water treated with polyphosphate can be heated up to a max temperature of 75° - 80°C, beyond that temperature the polyphosphate gradually loses its efficacy.

## SPECIFICATIONS

Non-toxic materials, suitable for drinking water.  
Head / ring nut: reinforced polypropylene.  
Bowl: SAN.  
O-ring: EPDM.  
IN/OUT brass threads: CW 617 N brass.



## 3 PORTS HEADS

DOSAFOS MIGNON PLUS 3P with polyphosphate loose crystals

### HOUSINGS WITH BRASS BSP THREADS

CODE	MODEL	APPLICABLE REFILL	g*	IN/OUT	DIMENSIONS mm		
					A	B	C
RA404P411	DOSAFOS MIGNON PLUS SL3P MFO	LOOSE CRYSTALS	265	1/2"	187	92	83


g\* = polyphosphate crystals amount in grams



DOSAFOS MIGNON PLUS 3P with HA polyphosphate crystals cartridge

### HOUSINGS WITH BRASS BSP THREADS

CODE	MODEL	SUITABLE CARTRIDGE	IN/OUT	DIMENSIONS mm		
				A	B	C
RA404P414	DOSAFOS MIGNON PLUS SL3P MFO + HA	HA 5" M SX CARTRIDGE	1/2"	187	92	83



DOSAFOS MIGNON PLUS 2P with polyphosphate loose crystals

### HOUSINGS WITH BRASS BSP THREADS

CODE	MODEL	APPLICABLE REFILL	g*	IN/OUT	DIMENSIONS mm		
					A	B	C
RA403P414	DOSAFOS MIGNON PLUS SL2P MFO	LOOSE CRYSTALS	275	1/2"	192	92	83

g\* = polyphosphate crystals amount in grams



DOSAFOS MIGNON PLUS 2P with HA polyphosphate crystals cartridge

### HOUSINGS WITH BRASS BSP THREADS

CODE	MODEL	SUITABLE CARTRIDGE	IN/OUT	DIMENSIONS mm		
				A	B	C
RA403P424	DOSAFOS MIGNON PLUS SL2P MFO + HA	HA 5" M SX CARTRIDGE	1/2"	192	92	83